BPN-350V2-SS



















Introduction

The BPN-350V2-SS is a mobile rack for the mainstream hard disk drive on the market today. It supports up to five SAS/SATA HDDs and can be applied for different RAID functions. With this device, hard disk drives can be installed and replaced at any time without the need to take off the PC casing. Also, the aluminum design and built-in cooling fan definitely help heat dissipate. The BPN-350V2-SS offers an economical removable storage solution.

Features

- Ideal for 5 Drive RAID Configurations
- · Lockable Design to Avoid Accidental Removal
- Two 60mm Cooling Fan for Reliable Thermal Solution
- · Hot Swappable Ability
- Multi-functional LED Indication
- Support 3.5" SAS I/II & SATA I/II/III HDDs
- Data Transfer Rate up to 6.0Gb/s

Specifications

Hot Swap	5x3.5"HDD
Cooling Fan [optional]	2x60mm
Standard Drive Bays	5.25" Drive: 3
Dimension (W x H x D)	5.8 x 5 x 7.5 inches 147 x 127 x 190 mm
Material	Aluminum Body
Power Connector	2x Molex
LED Display	Blue for Power on Red for HDD Access
Model Number in Different Color Handle	Black: BPN-350V2-SS Red: BPN-350V2-SS-RED

BPU-2535

1 x 3.5" to 2 x 2.5" SATA Hot-Swap Mobile Cage













Introduction

The BPU-2535 internal drive cage is a compact and cost effective solution for an internal 3.5" drive cage with two 2.5" drive bays. It provides an extra storage within a compact design to satisfy many application needs. The BPU-2535 is constructed of aluminum material that provides best heat dissipation required for high performance 2.5" laptop SATA drives. With mirroring technique (RAID 1), the BPU-2535 is able to maintain data in two disk drives simultaneously, which provides extra protection on critical data backup.

Features

- · Aluminum Frame
- · Hard Drive Interface: SATA I/II
- Form Factor: 1 x 3.5" Bay for 2 x 2.5" Hard Disk Drives
- High Performance Transfer Rate up to 3.0 Gbps
- · Support RAID 0 and 1 Functions (need an additional RAID controller)
- · Point to Point, Free from Master/ Slave Setting
- With one 4Pin Power and two 7Pin Signal Connectors
- Energy Saving on Using 2.5" HDDs or SSD
- · LED Indicators for Power & HDD access

Specifications

Hot Swap	2x2.5"HDD
Standard Drive Bays	3.5" Drive: 1
Dimension (W x H x D)	3.98 x 0.98 x 5.75 inches
Material	Aluminum Body
HDD Interface	SATA
Weight	0.6 lbs
Packaging Information	Enclosure, SATA Cables, Manual